



Dear Customer

Thank you for purchasing Lopolights unique navigation lights.
The Lopolight products are covered by a 5-year limited warranty.
Read more about Lopolight at www.lopolight.com.

Distributors:

Australia: Southern Seas Marine, sales@southernseasmarine.com, + 61 7 55029666. **Benelux:** Sailtron b.v., sailtron@sailtron.com, +31 (0)30-2840850.
Canada: Stright-MacKay Ltd., info@stright-mackay.com, +1 (902) 928-1900. **Denmark:** Polaris Electronics A/S, info@polaris-as.dk, +45 9631 7900.
Finland: OY Vestek AB, vestek@vestek.fi, +358 9 887 0120. **France:** Grément Import, info@wanadoo.fr, +33 (0) 228 030101. **Germany:** Peter Frisch GmbH, info@frisch.de, +49 89 36 50 75. **Italy:** Tomasoni Topsail S.p.A., group@tomasoni.com, +39 0185 2001. **New Zealand:** Enertec Marine Systems, info@enertecservices.co.nz, +64 9 414 4730. **Norway:** Polaris Electronics Norge AS, mail@polaris-as.no, +47 23 06 93 40. **Portugal:** NautiRadar, comercial@nautiradar.pt, +351 21300 5050. **Slovenia/Croatia:** DNA - Miha Špendal, x-yahts-jadran@siol.com, +386 41 730 970. **South Africa:** Manex & Power Marine, +21 511 7292, manex@manex.co.za. **Spain:** Yatess Servicios Nauticos S.L., +34 971 730175, yatess@yatess.com. **Sweden:** Cordland Marine AB, cordland@cordland.se, +46 (0)340-658970. **U.A.E.:** Exalto Emirates Ltd, info@exalto-emirates.com, +971-(0)6-5240597. **UK:** IMP, sales@improducts.co.uk, +44 (0)1763 241300. **USA:** Euro Marine Trading Inc., sales@euromarinetrading.com, +1 (401) 849 0060.
Other markets: Lopolight ApS, info@lopolight.com, +45 3248 5030, Ved Klaedebo 12B, DK-2970 Hoersholm, Denmark

Connect the power cable terminals - The ring terminals should be soldered onto the wires to ensure the best possible connection – DO NOT SOLDER ONTO A TERMINAL THAT IS BOLTED ONTO THE LOPOLIGHT. The heat may destroy the internal electronics. Other connection methods can be used – but soldering is the most reliable.

Make sure polarity is correct - Your Lopolight LED nav-light will only function if the polarity is correct. Please ensure that the "+" wire is connected to the terminal marked "+" (or 10-32 Volt) All Lopolight products accept any voltage between 10 and 32 Volt.

Waterproofing the terminals - Use a small amount of Sikaflex or 3M '5200' to cover all terminals. Place a small piece of soft plastic ("vita-wrap") on the silicone before mounting the lid.

The navigations light should not be grounded-

Troubleshooting:

If the light does not function:

Check that you have a voltage between 10 and 32 volts
and check that the polarity is right